

QGWQ(D) SERIES

S/S SUBMERSIBLE PUMP

S/S潜水泵

用途:

用于排污管径较小、排污距离较长的村庄、农场、别墅等无大口径排污管道的地方。一般住宅、娱乐场所等含各种污物、布料、纤维、毛巾等排污场合。

Scope of application:

Used in villages, farms, villas, and other places without large diameter sewage pipes, where the diameter of the sewage pipe is small and the distance of the sewage discharge is long. Generally, residential and entertainment venues contain various pollutants, fabrics, fibers, towels, and other pollutants.



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
220V/380V							
50WQD15-7-1.1QG	1.1	1.5	220	15	250	7	50
50WQD15-10-1.5QG	1.5	2	220	15	250	10	50
65WQD25-7-1.5QG	1.5	2	220	25	416	7	65
50WQD15-18-2.2QG	2.2	2.9	220	15	250	18	50
65WQD25-15-2.2QG	2.2	2.9	220	25	416	15	65
80WQD30-10-2.2QG	2.2	2.9	220	30	500	10	80
QGWQ15-7-1.1S	1.1	1.5	380	15	250	7	50
QGWQ15-10-1.5S	1.5	2	380	15	250	10	50
QGWQ25-7-1.5S	1.5	2	380	25	416	7	65
QGWQ15-18-2.2S	2.2	2.9	380	15	250	18	50
QGWQ25-15-2.2S	2.2	2.9	380	25	416	15	65
QGWQ30-10-2.2S	2.2	2.9	380	30	500	10	80
QGWQ15-20-3S	3	4	380	15	250	20	50
QGWQ30-17-3S	3	4	380	30	500	17	65
QGWQ35-14-3S	3	4	380	35	583	14	80
QGWQ15-25-4S	4	5	380	15	250	25	50
QGWQ45-17-4S	4	5	380	45	750	17	65
QGWQ60-13-4S	4	5	380	60	1000	13	80
QGWQ80-10-4S	4	5	380	80	1333	10	100
QGWQ65-17-5.5S	5.5	7.3	380	65	1083	17	80
QGWQ85-15-5.5S	5.5	7.3	380	85	1416	15	100
QGWQ85-19-7.5S	7.5	10	380	85	1416	19	80
QGWQ100-15-7.5S	7.5	10	380	100	1666	15	100
QGWQ100-20-11S	11	14.7	380	100	1666	20	100
QGWQ150-11-11S	11	14.7	380	150	2500	11	150
QGWQ100-25-15S	15	20	380	100	1666	25	100
QGWQ150-15-15S	15	20	380	150	2500	15	150

JYWQ(D) SERIES

S/S SUBMERSIBLE PUMP

S/S潜水泵

用途:

该系列电泵主要适用于化工、石油、制药、采矿、造纸工业、水泥厂、炼钢厂、电厂、煤加工工业，以及城市污水处理厂排水系统、市政工程、建筑工地等行业输送带颗粒的污水、污物，也可用于抽送清水及带腐蚀性介质。

Scope of application:

This series of electric pumps is mainly suitable for conveying granular wastewater and pollutants in industries such as chemical, petroleum, pharmaceutical, mining, papermaking, cement plants, steel mills, power plants, coal processing, as well as urban sewage treatment plant drainage systems, municipal engineering, construction sites, etc. It can also be used to pump clean water and corrosive media.



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
220V/380V							
80WQ40-18-4S	4	5	380	40	666	18	80
100WQ50-15-4S	4	5	380	50	833	15	100
50WQ20-32-5.5S	5.5	7.3	380	20	333	32	50
65WQ30-25-5.5S	5.5	7.3	380	30	500	25	65
80WQ50-18-5.5S	5.5	7.3	380	50	833	18	80
100WQ80-10-5.5S	5.5	7.3	380	80	1333	10	100
150WQ100-7-5.5S	5.5	7.3	380	100	1666	7	150
50WQ20-40-7.5S	7.5	10	380	20	333	40	50
65WQ30-32-7.5S	7.5	10	380	30	500	32	65
80WQ45-22-7.5S	7.5	10	380	45	750	22	80
100WQ80-15-7.5S	7.5	10	380	80	1333	15	100
150WQ100-10-7.5S	7.5	10	380	100	1666	10	150
65WQ30-50-11S	11	14.7	380	30	500	50	65
80WQ45-42-11S	11	14.7	380	45	750	42	80
100WQ100-20-11S	11	14.7	380	100	1666	20	100
150WQ180-11-11S	11	14.7	380	180	3000	11	150
65WQ30-60-15S	15	20	380	30	500	60	65
80WQ45-52-15S	15	20	380	45	750	52	80
100WQ100-25-15S	15	20	380	100	1666	25	100
150WQ180-15-15S	15	20	380	180	3000	15	150