

SPA SERIES

SUBMERSIBLE SEWAGE PUMPS SERIES

潜水排污泵



工作条件:

1. 输送介质的温度不应高于40℃
2. 介质的pH范围为4~10。
3. 介质的运动粘度为: $7 \times 10^{-7} \sim 23 \times 10^{-6} \text{m}^2/\text{s}$;
4. 输送介质的最大密度为 $12 \times 10^3 \text{kg/m}^3$ 。

Working conditions:

1. The trans medium's temperature shouldn't be higher than 40℃
2. The trans medium's pH scope is from 4~10.
3. The kinematic viscosity of the trans medium is: $7 \times 10^{-7} \sim 23 \times 10^{-6} \text{m}^2/\text{s}$;
4. The maximum density of trans medium is $12 \times 10^3 \text{kg/m}^3$.

技术参数 / Technical parameters

型号 Model	功率 power		额定流量 Rate Flow		扬程 Head m	转速 Speed r/min	口径 Outlet mm
	Kw	HP	m³/h	L/min			
SPA6-28/2-1.1	1.1	1.5	6	100	28	2900	50
SPA6-39/3-1.5	1.5	2	6	100	39	2900	50
SPA6-52/4-2.2	2.2	3	6	100	52	2900	50

QD SERIES

SUBMERSIBLE PUMPS

潜水泵



产品特点:

QD型潜水泵电机位于电动泵的上部，为离心式叶轮，蜗壳结构；泵和电机采用双端面机械密封。该系列水泵由于体积小、重量轻，特别适用于地下抽水、灌溉、养殖排水、花园浇水以及宾馆、食堂、高层建筑等场所用水。

Product Features:

QD submersible pump motor is located in the upper part of the electric pump, for the centrifugal impeller, the spiral case structure; the pump and the motor adopts the double end face mechanical seal. This series pump is due to the small size, light weight, particularly suitable for underground pumping, irrigation, aquaculture Aerobics in water supply and drainage, garden watering and hotels, canteens, high-rise buildings and other places water use.



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
QYD3-36/2-1.1	1.1	1.5	220	3	50	36	50
QY3-36/2-1.1	1.1	1.5	380	3	50	36	50
QYD3-48/3-1.5	1.5	2	220	3	50	48	50
QY3-48/3-1.5	1.5	2	380	3	50	48	50
QYD3-65/4-1.8	1.8	2.5	220	3	50	65	50
QY3-65/4-1.8	1.8	5.5	380	3	50	65	50
QYD3-80/5-2.2	2.2	3	220	3	50	80	50
QY3-80/5-2.2	2.2	3	380	3	50	80	50
QYD3-96/6-3	3	4	220	3	50	96	50
QY3-96/6-3	3	4	380	3	50	96	50
QYD10-26/2-1.8	1.8	2.5	220	10	166	26	50
QY10-26/2-1.8	1.8	2.5	380	10	166	26	50
QYD10-45/3-2.2	2.2	3	220	10	166	45	50
QY10-45/3-2.2	2.2	3	380	10	166	45	50
QYD10-55/4-3	3	4	220	10	166	55	50
QY10-55/4-3	3	4	380	10	166	55	50

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
50QY15-26-2.2	2.2	3	380	15	250	26	50
65QY25-17-2.2	2.2	3	380	25	416	17	65
80QY40-12-2.2	2.2	3	380	40	666	12	80
100QY65-7-2.2	2.2	3	380	65	1083	7	100
150QY100-4.5-2.2	2.2	3	380	100	1666	4.5	150
50QY15-36-3	3	4	380	15	250	36	50
65QY25-26-3	3	4	380	25	416	26	65
80QY40-16-3	3	4	380	40	666	16	80
100QY65-10-3	3	4	380	65	1083	10	100
150QY150-6-3	3	4	380	150	2500	6	150
65QY20-36/2-3	3	4	380	20	333	36	65
50QY10-54/3-3	3	4	380	10	166	54	50
65QY30-32-3.5	3.5	4.5	380	30	500	32	65
80QY40-19-3.5	3.5	4.5	380	40	666	19	80
50QY15-50-4	4	5.5	380	15	250	50	50
65QY25-32-4	4	5.5	380	25	416	32	65
65QY30-35-4	4	5.5	380	30	500	35	65
80QY40-21-4	4	5.5	380	40	666	21	80
100QY65-14-4	4	5.5	380	65	1083	14	100
150QY100-9-4	4	5.5	380	100	1666	9	150
150QY200-6-4	4	5.5	380	200	3333	6	150
200QY250-5-4	4	5.5	380	250	4166	5	200
65QY25-42/2-4	4	5.5	380	25	416	42	65
50QY10-60/2-4	4	5.5	380	10	166	60	50



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
50QY10-72/4-4	4	5.5	380	10	166	72	50
65QY20-58/3-4.5	4.5	6	380	20	333	58	65
80QY40-25-4.5	4.5	6	380	40	666	25	80
65QY25-54/3-5.5	5.5	7.5	380	25	416	54	65
50QY10-85/3-5.5	5.5	7.5	380	10	166	85	50
65QY20-62/3-5.5	5.5	7.5	380	20	333	62	65
65QY25-50/2-5.5	5.5	7.5	380	25	416	50	65
65QY25-42-5.5	5.5	7.5	380	25	416	42	65
80QY40-28-5.5	5.5	7.5	380	40	666	28	80
100QY65-20-5.5	5.5	7.5	380	65	1083	20	100
150QY160-10-5.5	5.5	7.5	380	160	2666	10	150
150QY200-8-5.5	5.5	7.5	380	200	3333	8	150
200QY250-6-5.5	5.5	7.5	380	250	4166	6	200
50QY10-110/4-7.5	7.5	10	380	10	166	110	50
65QY25-60/2-7.5	7.5	10	380	25	416	60	65
65QY20-85/4-7.5	7.5	10	380	20	333	85	65
65QY25-50-7.5	7.5	10	380	25	416	50	65
80QY40-38-7.5	7.5	10	380	40	666	38	80
100QY65-25-7.5	7.5	10	380	65	1083	25	100
150QY160-13-7.5	7.5	10	380	160	2666	13	150
150QY200-12-7.5	7.5	10	380	200	3333	12	150
200QY260-8-7.5	7.5	10	380	260	4333	8	200
250QY350-5-7.5	7.5	10	380	350	5833	5	250
50QY10-165/6-11	11	15	380	10	166	165	50
65QY20-130/6-11	11	15	380	20	333	130	65
65QY25-90/3-11	11	15	380	25	416	90	65
80QY40-58/2-11	11	15	380	40	666	58	80
100QY65-42/2-11	11	15	380	65	1083	42	100
100QY100-25-11	11	15	380	100	1666	25	100
150QY200-15-11	11	15	380	200	3333	15	150
200QY250-10-11	11	15	380	250	4166	10	200
250QY400-7-11	11	15	380	400	6666	7	250
50QY10-220/8-15	15	20	380	10	166	220	50
65QY25-120/4-15	15	20	380	25	416	120	65
80QY40-84/3-15	15	20	380	40	666	84	80
100QY65-60/3-15	15	20	380	65	1083	60	100
100QY65-50/2-15	15	20	380	65	1083	50	100
100QY80-45-15	15	20	380	80	1333	45	100
150QY160-25-15	15	20	380	160	2666	25	150
200QY250-15-15	15	20	380	250	4166	15	200
250QY400-9-15	15	20	380	400	6666	9	250