

Q(D)X/WQ Series

S/S SUBMERSIBLE PUMP

S/S潜水泵



Q(D)X



WQ(D)



WQ(D)

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow	扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h L/min	m	mm
QDX3-6-0.25S	0.25	0.3	220	3 50	6	25
Q(D)X1.5-14-0.37S	0.37	0.5	220/380	1.5 25	14	25
Q(D)X3-12-0.37S	0.25	0.3	220/380	3 50	12	32
Q(D)X1.5-18-0.55S	0.55	0.7	220/380	1.5 25	18	25
Q(D)X3-16-0.55S	0.55	0.7	220/380	3 50	16	32
Q(D)X6-10-0.55S	0.55	0.7	220/380	6 100	10	40
Q(D)X8-8-0.55S	0.55	0.7	220/380	8 133	8	50
Q(D)X1.5-22-0.75S	0.75	1	220/380	1.5 25	22	25
Q(D)X3-20-0.75S	0.75	1	220/380	3 50	20	32
Q(D)X7-18-0.75S	0.75	1	220/380	7 117	18	40
Q(D)X10-15-0.75S	0.75	1	220/380	10 167	15	50
Q(D)X1.5-30-1.1S	1.1	1.5	220/380	1.5 25	30	25
Q(D)X3-26-1.1S	1.1	1.5	220/380	3 50	26	32
Q(D)X12-15-1.1S	1.1	1.5	220/380	12 200	15	40
Q(D)X18-12-1.1S	1.1	1.5	220/380	18 300	12	50

型号 Model	功率 power		电压 voltage	流量 Flow	扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h L/min	m	mm
WQ(D)3-8-0.37S	0.37	0.5	220/380	3 50	8	25
WQ(D)4-7-0.37S	0.37	0.5	220/380	4 67	7	32
WQ(D)4-10-0.55S	0.55	0.7	220/380	4 67	10	25
WQ(D)7-7-0.55S	0.55	0.7	220/380	7 117	7	50
WQ(D)5-15-0.75S	0.75	1	220/380	5 83	15	32
WQ(D)7-10-0.75S	0.75	1	220/380	7 117	10	50
WQ(D)7-15-1.1S	1.1	1.5	220/380	7 117	15	40
WQ(D)10-10-1.1S	1.1	1.5	220/380	10 167	10	50

型号 Model	功率 power		电压 voltage	流量 Flow	扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h L/min	m	mm
WQD8-12-0.75S	0.75	1	220	8 133	12	40
WQD10-9-0.75S	0.75	1	220	10 167	9	50
WQD10-14-1.1S	1.1	1.5	220	10 167	14	40
WQD12-12-1.1S	1.1	1.5	220	12 200	12	50
WQD12-15-1.5S	1.5	2	220	12 200	15	40
WQD15-12-1.5S	1.5	2	220	15 250	12	50
WQ8-12-0.75S	0.75	1	380	8 133	12	40
WQ10-9-0.75S	0.75	1	380	10 167	9	50
WQ10-14-1.1S	1.1	1.5	380	10 167	14	40
WQ12-12-1.1S	1.1	1.5	380	12 200	12	50
WQ12-15-1.5S	1.5	2	380	12 200	15	40
WQ15-12-1.5S	1.5	2	380	15 250	12	50
WQ9-22-2.2S	2.2	2.9	380	9 150	22	40
WQ15-18-2.2S	2.2	2.9	220	15 250	18	50

Q(D)X/WQ Series

S/S SUBMERSIBLE PUMP

S/S潜水泵



Q(D)X



WQ(D)

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
QDX1.5-15-0.37S	0.37	0.5	220	1.5	25	15	25
QDX3-18-0.55S	0.55	0.7	220	3	50	18	25
QDX6-14-0.55S	0.55	0.7	220	6	100	14	40
QDX10-10-0.55S	0.55	0.7	220	10	167	10	50
QDX3-24-0.75S	0.75	1	220	3	50	24	25
QDX6-18-0.75S	0.75	1	220	6	100	18	40
QDX10-13-0.75S	0.75	1	220	10	167	13	50
QDX6-24-1.1S	1.1	1.5	220	6	100	24	40
QDX10-18-1.1S	1.1	1.5	220	10	167	18	50
QDX6-32-1.5S	1.5	2	220	6	100	32	40
QDX10-24-1.5S	1.5	2	220	10	167	24	50
QX1.5-15-0.37S	0.37	0.5	380	1.5	25	15	25
QX3-18-0.55S	0.55	0.7	380	3	50	18	25
QX6-14-0.55S	0.55	0.7	380	6	100	14	40
QX10-10-0.55S	0.55	0.7	380	10	167	10	50
QX3-24-0.75S	0.75	1	380	3	50	24	25
QX6-18-0.75S	0.75	1	380	6	100	18	40
QX10-13-0.75S	0.75	1	380	10	167	13	50
QX6-24-1.1S	1.1	1.5	380	6	100	24	40
QX10-18-1.1S	1.1	1.5	380	10	167	18	50
QX6-32-1.5S	1.5	2	380	6	100	32	40
QX10-24-1.5S	1.5	2	380	10	167	24	50

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
25WQD3-7-0.25S	0.25	0.3	220	3	50	7	25
40WQD7-3-0.25S	0.25	0.3	220	7	116	3	40
25WQD3-9-0.37S	0.37	0.5	220	3	50	9	25
40WQD7-5-0.37S	0.37	0.5	220	7	116	5	40
25WQD3-12-0.55S	0.55	0.7	220	3	50	12	25
50WQD10-6-0.55S	0.55	0.7	220	10	167	6	40
40WQD10-9-0.75S	0.75	1	220	10	167	9	40
50WQD12-8-0.75S	0.75	1	220	12	200	8	50
40WQD8-15-1.1S	1.1	1.5	220	8	133	15	40
50WQD12-12-1.1S	1.1	1.5	220	12	200	12	50
40WQD10-16-1.5S	1.5	2	220	10	167	16	40
50WQD15-12-1.5S	1.5	2	220	15	250	12	50
25WQ3-7-0.25S	0.25	0.3	380	3	50	7	25
40WQ7-3-0.25S	0.25	0.3	380	7	116	3	40
25WQ3-9-0.37S	0.37	0.5	380	3	50	9	25
40WQ7-5-0.37S	0.37	0.5	380	7	116	5	40
25WQ3-12-0.55S	0.55	0.7	380	3	50	12	25
50WQ10-6-0.55S	0.55	0.7	380	10	167	6	40
40WQ10-9-0.75S	0.75	1	380	10	167	9	40
50WQ12-8-0.75S	0.75	1	380	12	200	8	50
40WQ8-15-1.1S	1.1	1.5	380	8	133	15	40
50WQ12-12-1.1S	1.1	1.5	380	12	200	12	50
65WQ20-6-1.1S	1.1	1.5	380	20	333	6	65
40WQ10-16-1.5S	1.5	2	380	10	167	16	40
50WQ15-12-1.5S	1.5	2	380	15	250	12	50
65WQ25-7-1.5S	1.5	2	380	25	416	7	65
50WQ15-20-2.2S	2.2	2.9	380	15	250	20	50
65WQ25-15-2.2S	2.2	2.9	380	25	416	15	65

Q(D)X/WQ Series

S/S SUBMERSIBLE PUMP

S/S潜水泵



WQ(D)



WQ(D)

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
WQD10-10-0.75S	0.75	1	220	10	166	10	50
WQD15-10-1.1S	1.1	1.5	220	15	250	10	50
WQD15-15-1.5S	1.5	2	220	15	250	15	50
WQ10-10-0.75S	0.75	1	380	10	166	10	50
WQ15-10-1.1S	1.1	1.5	380	15	250	10	50
WQ15-15-1.5S	1.5	2	380	15	250	15	50

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
60WQD10-10-0.75S	0.75	1	220	10	166	10	50
65WQD15-6-0.75S	0.75	1	220	15	250	6	65
50WQD15-10-1.1S	1.1	1.5	220	15	250	10	50
65WQD20-6-1.1S	1.1	1.5	220	20	333	6	65
50WQD15-15-1.5S	1.5	2	220	15	250	15	50
65WQD25-7-1.5S	1.5	2	220	25	416	7	65
50WQ10-10-0.75S	0.75	1	380	10	166	10	50
65WQ15-6-0.75S	0.75	1	380	15	250	6	65
50WQ15-10-1.1S	1.1	1.5	380	15	250	10	50
65WQ20-6-1.1S	1.1	1.5	380	20	333	6	65
50WQ15-15-1.5S	1.5	2	380	15	250	15	50
65WQ25-7-1.5S	1.5	2	380	25	416	7	65
50WQ15-20-2.2S	2.2	2.9	380	15	250	20	50
65WQ25-15-2.2S	2.2	2.9	380	25	416	15	65
80WQ40-9-2.2S	2.2	2.9	380	40	666	9	80
100WQ50-7-2.2S	2.2	2.9	380	50	833	7	100
50WQ15-25-3S	3	4	380	15	250	25	50
65WQ25-20-3S	3	4	380	25	416	20	65
80WQ40-15-3S	3	4	380	40	666	15	80
100WQ50-10-3S	3	4	380	50	833	10	100
50WQ15-32-4S	4	5	380	15	250	32	50
65WQ25-25-4S	4	5	380	25	416	25	65

Q(D)X/WQ Series

S/S SUBMERSIBLE PUMP

S/S潜水泵



WQ(D)



QGWQ(D)

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
80WQ40-18-4S	4	5	380	40	666	18	80
100WQ50-15-4S	4	5	380	50	833	15	100
50WQ20-32-5.5S	5.5	7.4	380	20	333	32	50
65WQ30-25-5.5S	5.5	7.4	380	30	500	25	65
80WQ50-18-5.5S	5.5	7.4	380	50	833	18	80
100WQ80-10-5.5S	5.5	7.4	380	80	1333	10	100
150WQ100-7-5.5S	5.5	7.4	380	100	1666	7	150
50WQ20-40-7.5S	7.5	10	380	20	333	40	50
65WQ30-32-7.5S	7.5	10	380	30	500	32	65
80WQ45-22-7.5S	7.5	10	380	45	750	22	80
100WQ80-15-7.5S	7.5	10	380	80	1333	15	100
150WQ100-10-7.5S	7.5	10	380	100	1666	10	150
65WQ30-50-11S	11	15	380	30	500	50	65
80WQ45-42-11S	11	15	380	45	750	42	80
100WQ100-20-11S	11	15	380	100	1666	20	100
150WQ180-11-11S	11	15	380	180	3000	11	150
65WQ30-60-15S	15	20	380	30	500	60	65
80WQ45-52-15S	15	20	380	45	750	52	80
100WQ100-25-15S	15	20	380	100	1666	25	100
150WQ180-15-15S	15	20	380	180	3000	15	150

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
220V/380V	Kw	HP	V	m³/h	L/min	m	mm
GNWQD15-6-0.75S	0.75	1	220	15	250	6	50
GNWQD15-7-1.1S	1.1	1.5	220	15	250	7	50
GNWQD15-10-1.5S	1.5	2	220	15	250	10	50
GNWQ15-6-0.75S	0.75	1	380	15	250	6	50
GNWQ15-7-1.1S	1.1	1.5	380	15	250	7	50
GNWQ15-10-1.5S	1.5	2	380	15	250	10	50