

WB/BZ SERIES

SELF-PRIMING CLEAN CENTRIFUGAL PUMP

离心式自吸（清水）

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	额定流量 Rated flow		额定扬程 rated head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
40BZ-20	1.5	2	380	10	166	20	40
50BZ-25	2.2	3	380	10	166	25	50
65BZ-15	2.2	3	380	20	333	15	65
50BZ-32	3	4	380	10	266	32	50
65BZ-20	3	4	380	25	416	20	65
50BZ-35	4	5	380	14	233	35	50
65BZ-30	4	5	380	25	416	30	65
50BZ-50	5.5	7.4	380	20	333	50	50
65BZ-40	5.5	7.4	380	25	416	40	65
80BZ-30	7.5	10	380	50	833	30	80
100BZ-20	7.5	10	380	100	1666	20	100
80BZ-40	11	15	380	48	800	40	80
100BZ-35	11	15	380	100	1666	35	100
80BZ-50	15	20	380	65	1083	50	80
100BZ-45	15	20	380	100	1666	45	100
100BZ-55	18.5	25	380	100	1666	55	100
100BZ-65	22	30	380	100	1666	65	100



50WB10-16Z


(Twin impeller)
50WB12-28Z


50WB8-15Z

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
40WB6-15D	0.55	0.7	220	6	100	15	40
40WB8-16D	0.75	1	220	8	133	16	40
50WB10-16Z	0.55	1.7	220	10	166	16	50
50WB12-16Z	0.75	1	220	12	200	16	50
75WB35-10Z	2.2	3	220	35	583	10	75
50WB12-28Z	2.2	3	220	12	200	28	50
50WB8-10Z	1.1	1.5	220	8	133	10	50
50WB8-15Z	1.5	2	220	8	133	15	50

ZW(M SERIES)

SELF SUCTION SEWAGE PUMP

联体自吸（污水）泵



ZW


(couple motor)
ZWM

技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	流量 Flow		扬程 Head	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	mm
40ZW8-15	1.5	2	380	8	133	15	40
50ZW10-20	2.2	3	380	10	166	20	50
50ZW15-30	3.0	4	380	15	250	30	50
65ZW20-20	3.0	4	380	20	333	20	65
65ZW20-25	4.0	5	380	20	333	25	65
80ZW35-20	4.0	5	380	35	583	20	80
65ZW20-30	5.5	7.4	380	20	333	30	65
80ZW40-22	5.5	7.4	380	40	666	22	80
80ZW65-25	7.5	10	380	65	1083	25	80
100ZW90-20	7.5	10	380	90	1500	20	100
65ZW40-50	11	15	380	40	666	50	65
100ZW100-20	11	15	380	100	1666	20	100
80ZW80-35	15	20	380	80	1333	35	80
100ZW70-35	15	20	380	70	1166	35	100
80ZW80-45	18.5	25	380	80	1333	45	80
100ZW100-30	22	30	380	100	1666	30	100
100ZW80-45	30	40	380	80	1333	45	100
100ZW100-65	37	50	380	100	1666	65	100
65ZW30-18	4-4	5-5	380	30	500	18	65
80ZW40-16	4-4	5-5	380	40	666	16	80
100ZW100-15	7.5-4	10-5	380	100	1666	15	100
150ZW180-10	11-4	15-5	380	180	3000	11	150
150ZW180-14	15-4	20-5	380	180	3000	14	150
150ZW180-17	18.5-4	25-5	380	180	3000	17	150
150ZW180-20	22-2	30-3	380	180	3000	20	150