

WBZ(S) SERIES

ALL STAINLESS STEEL CORROSION-RESISTANT
SELF PRIMING MICRO ELECTRIC PUMP
全不锈钢耐腐蚀自吸微型电动泵



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	额定流量 Rated flow		额定扬程 rated head	转速 Speed	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	r/min	mm
25WBZ3-10	0.25	0.3	220	3	50	10	2860	25
25WBZ3-10	0.37	0.5	220	3	50	10	2860	25
25WBZ3-18	0.55	0.7	220	3	50	18	2860	25
25WBZ6-18	0.75	1	220	6	100	18	2860	25
40WBZ10-18	1.1	1.5	220	10	166	18	2860	40
40WBZ13-18	1.5	2	220	13	216	18	2860	40
25WBZ3-10	0.25	0.3	380	3	50	10	2860	25
25WBZ3-10	0.37	1.5	380	3	50	10	2860	25
25WBZ3-18	0.55	1.7	380	3	50	18	2860	25
25WBZ6-18	0.75	1	380	6	100	18	2860	25
40WBZ10-18	1.1	1.5	380	10	166	18	2860	40
40WBZ13-18	1.5	2	380	13	216	18	2860	40
50WBZS13.5-22	2.2	3	380	13.5	225	22	2860	50
50WBZS15-22	3	4	380	15	250	22	2860	50



型号 Model	功率 power		电压 voltage	额定流量 Rated flow		额定扬程 rated head	转速 Speed	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	r/min	mm
25WBZ3-8	0.25	0.3	220	3	50	8	2860	32/25
25WBZ3-8	0.37	0.5	220	3	50	8	2860	32/25
25WBZ6-13	0.55	0.7	220	6	100	13	2860	40/32
25WBZ5-20	0.75	1	220	5	83	20	2860	40/32
40WBZ10-16	1.1	1.5	220	10	166	16	2860	50/40
40WBZ15-18	1.5	2	220	15	250	18	2860	50/40
50WBZ13.5-22	2.2	3	220	13.5	225	22	2860	50/40
25WBZ3-8	0.25	0.3	380	3	50	8	2860	32/25
25WBZ3-8	0.37	0.5	380	3	50	8	2860	32/25
25WBZ6-13	0.55	0.7	380	6	100	13	2860	40/32
25WBZ5-20	0.75	1	380	5	83	20	2860	40/32
40WBZ10-16	1.1	1.5	380	10	166	16	2860	50/40
40WBZ15-18	1.5	2	380	15	250	18	2860	50/40
50WBZS13.5-22	2.2	3	380	13.5	225	22	2860	50/40
50WBZS15-22	3	4	380	15	250	22	2860	50/40

TBKM SERIES

OPEN IMPELLER
开式叶轮



技术参数 / Technical parameters

型号 Model	进口/出口 Inlet/outlet	功率 power		Q	0	6	12	18	24	36	42	54	66	108
单相 Single phase	Inch	KW	HP	m³/h	0	100	200	300	400	600	700	900	1100	1800
TBkm150	2"x2"	1.1	1.5			9.5	8.9	7.9	6.9	5.4				
TBkm200	2"x2"	1.5	2.0	H		12.7	12.3	11.5	10.5	9.0	5.8			
TBkm300	2.5"x2"	2.2	3.0	m		15	14.5	13.8	12.9	12.1	9.7			
TBkm400	2.5"x2"	3.0	4.0			17.5	16.9	16.3	15.6	14	12.4	9.3	7.6	

WBZ(S) SERIES

ALL STAINLESS STEEL SELF PRIMING
CORROSION-RESISTANT MICRO ELECTRIC
PUMP<EXPLOSION-PROOF SELF PRIMING PUMP
全不锈钢自吸耐腐蚀微电子泵-防爆自吸泵



技术参数 / Technical parameters

型号 Model	功率 power		电压 voltage	额定流量 Rated flow		额定扬程 rated head	转速 Speed	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	r/min	mm
25WBZS3-10	0.25	0.3	380	3	50	10	2900	25
25WBZS3-18	0.55	0.7	380	3	50	18	2900	25
25WBZS6-18	0.75	1	380	6	100	18	2900	25
40WBZS10-18	1.1	1.5	380	10	166	18	2900	40
40WBZS13-18	1.5	2	380	13	217	18	2900	40
50WBZS13.5-22	2.2	3	380	13.5	225	22	2900	50

型号 Model	功率 power		电压 voltage	额定流量 Rated flow		额定扬程 rated head	转速 Speed	口径 Outlet
	Kw	HP	V	m³/h	L/min	m	r/min	mm
25WB53-8	0.25	0.3	380	3	50	8	2900	25-25
25WB56-13	0.55	0.7	380	6	100	13	2900	40-25
25WB55-20	0.75	1	380	5	83	20	2900	40-25
40WB510-16	1.1	1.5	380	10	166	16	2900	50-40
40WB515-18	1.5	2	380	15	250	18	2900	50-40
50WB513.5-22	2.2	3	380	13.5	225	22	2900	50-40